

## CLAIMS

1. A fastener ring (1) for fastening a dispenser member (2), such as a pump or a valve, on a neck (30) of a receptacle (3) containing fluid to be dispensed, said  
5 fastener ring (1) includes deformable sealing means (10) that co-operate with said neck (30) of said receptacle (3) so as to fasten said dispenser member (2) in leaktight manner on said receptacle (3), said fastener ring being characterized in that said sealing means (10)  
10 comprise two deformable lips.
2. A fastener ring according to claim 1, in which said sealing means (10) comprise at least one elastically deformable lip.
- 15 3. A fastener ring according to any preceding claim, in which said sealing means (10) are made integrally with said fastener ring (1).
- 20 4. A fastener ring according to claim 1 or claim 2, in which said sealing means (10) are injection-molded onto said fastener ring (1).
- 25 5. A fastener ring according to any preceding claim, in which the ring (1) includes snap-fastener means (15) including a contact surface (115) that is adapted to co-operate with a shoulder surface (130) of said neck (30) of the receptacle (3), so as to fasten the dispenser member (2) on said receptacle (3), said contact and  
30 shoulder surfaces (115 and 130) being substantially radial.
- 35 6. A fastener ring according to any preceding claim, in which the ring (1) is made integrally with a turret (20) that is fastened to the dispenser member (2), and/or with a ferrule (11) defining the rest position of the dispenser member (2).

## AMENDED SHEET

7. A fluid dispenser device comprising a receptacle (3),  
and a dispenser member (2) such as a pump or a valve, the  
device being characterized in that it further comprises a  
5 fastener ring (1) according to any preceding claim.

8. A dispenser device according to claim 7, in which said  
sealing means (10) of the ring (1) fasten the dispenser  
member (2) in leaktight manner on the receptacle (3).  
10

9. A dispenser device according to claim 7 or claim 8, in  
which said neck (30) of the receptacle (3) includes an  
axially-projecting portion (31) that is suitable for co-  
operating with said deformable sealing means (10) of the  
15 fastener ring (1).

10. A dispenser device according to any one of claims 7  
to 9, in which said deformable sealing means (10) of the  
fastener ring (1) co-operate with said neck (30) of the  
20 receptacle (3) to define a leaktight-contact zone that  
provides the sealing, said leaktight-contact zone sloping  
at least in part.

11. A dispenser device according to any one of claims 7  
25 to 10, in which said fastener ring (1) makes it possible  
to compensate for any dimensional and/or geometrical  
variations in the neck (30) of the receptacle (3) that  
are linked to manufacturing tolerances.

\* \* \*

#### AMENDED SHEET

This translation of an amended page covers the amendments made in the original.  
However, the page breaks match the translation, so that this page is also a  
replacement page that fits in with the remainder of the translation.